



GO RETREAD

Highly performing and resistant, our comprehensive range of high quality carbide tungsten tools will provide you entire satisfaction for all your grinding and buffing needs!

Power Grinder Range

Multiple shapes available with different sizes of aggressive grits.

Possibility to produce customized products.

Carbide Contour Wheels



NS05-6836 NS05-6436 NS05-6624 NS05-6136

Ref No.	Diameter	Width	Bore	Grits
NS05-6160	2"(50mm)	3/4"(19mm)	3/8"(9.5mm)	60
NS05-6136	2"(50mm)	3/4"(19mm)	3/8"(9.5mm)	36
NS05-6124	2"(50mm)	3/4"(19mm)	3/8"(9.5mm)	24
NS05-6116	2"(50mm)	3/4"(19mm)	3/8"(9.5mm)	16
NS05-6460	2-3/16"(55mm)	1"(25mm)	3/8" x 24 thread	60
NS05-6436	2-3/16"(55mm)	1"(25mm)	3/8" x 24 thread	36
NS05-6424	2-3/16"(55mm)	1"(25mm)	3/8" x 24 thread	24
NS05-6416	2-3/16"(55mm)	1"(25mm)	3/8" x 24 thread	16
NS05-6660	2-9/16"(65mm)	1/2"(13mm)	3/8"(9.5mm)	60
NS05-6636	2-9/16"(65mm)	1/2"(13mm)	3/8"(9.5mm)	36
NS05-6624	2-9/16"(65mm)	1/2"(13mm)	3/8"(9.5mm)	24
NS05-6616	2-9/16"(65mm)	1/2"(13mm)	3/8"(9.5mm)	16
NS05-6860	3"(76mm)	1-1/4"(32mm)	9/16"(14mm)	60
NS05-6836	3"(76mm)	1-1/4"(32mm)	9/16"(14mm)	36
NS05-6824	3"(76mm)	1-1/4"(32mm)	9/16"(14mm)	24
NS05-6816	3"(76mm)	1-1/4"(32mm)	9/16"(14mm)	16

Carbide Unit Wheels



NS05-4036

Ref No.	Diameter	Width	Bore	Grits
NS05-4036	3"(76mm)	1"(25mm)	9/16"(14mm)	36
NS05-4024	3"(76mm)	1"(25mm)	9/16"(14mm)	24
NS05-4016	3"(76mm)	1"(25mm)	9/16"(14mm)	16

Carbide Brazed Wheels



Ref No.	Diameter	Width	Bore	Grits
NS05-8036	2"(50mm)	1/8"(3mm)	3/8" x 24 thread	36
NS05-8024	2"(50mm)	1/8"(3mm)	3/8" x 24 thread	24
NS05-8016	2"(50mm)	1/8"(3mm)	3/8" x 24 thread	16
NS05-8136	2"(50mm)	1/4"(6mm)	3/8" x 24 thread	36
NS05-8124	2"(50mm)	1/4"(6mm)	3/8" x 24 thread	24
NS05-8116	2"(50mm)	1/4"(6mm)	3/8" x 24 thread	16
NS05-8236	2"(50mm)	1/2"(13mm)	3/8" x 24 thread	36
NS05-8224	2"(50mm)	1/2"(13mm)	3/8" x 24 thread	24
NS05-8216	2"(50mm)	1/2"(13mm)	3/8" x 24 thread	16
NS05-8336	2"(50mm)	3/4"(20mm)	3/8" x 24 thread	36
NS05-8324	2"(50mm)	3/4"(20mm)	3/8" x 24 thread	24
NS05-8316	2"(50mm)	3/4"(20mm)	3/8" x 24 thread	16

Carbide Donut Wheels



Ref No.	Diameter	Width	Bore	Grits
NS05-2036	2-1/2"(63.5mm)	7/16"(11mm)	3/8"(9.5mm)	36
NS05-2024	2-1/2"(63.5mm)	7/16"(11mm)	3/8"(9.5mm)	24
NS05-2016	2-1/2"(63.5mm)	7/16"(11mm)	3/8"(9.5mm)	16

Carbide Tapered Cone Rasps



Ref No.	Diameter	Length	Bore	Grits
NS05-3360	1"(25mm)	2"(50mm)	3/8" x 24 thread	60
NS05-3336	1"(25mm)	2"(50mm)	3/8" x 24 thread	36
NS05-3324	1"(25mm)	2"(50mm)	3/8" x 24 thread	24
NS05-3316	1"(25mm)	2"(50mm)	3/8" x 24 thread	16
NS05-3460	3/4"(19mm)	4"(101mm)	3/8" x 24 thread	60
NS05-3436	3/4"(19mm)	4"(101mm)	3/8" x 24 thread	36
NS05-3424	3/4"(19mm)	4"(101mm)	3/8" x 24 thread	24
NS05-3416	3/4"(19mm)	4"(101mm)	3/8" x 24 thread	16

Carbide Pencil Rasps



Ref No.	Diameter	Length	Shaft	Grits
NS05-9460	1/4"(6.3mm)	4-1/2"(116mm)	1/4"(6.3mm)	60
NS05-9436	1/4"(6.3mm)	4-1/2"(116mm)	1/4"(6.3mm)	36
NS05-9424	1/4"(6.3mm)	4-1/2"(116mm)	1/4"(6.3mm)	24
NS05-9416	1/4"(6.3mm)	4-1/2"(116mm)	1/4"(6.3mm)	16
NS05-9660	3/8"(9.5mm)	4-1/2"(116mm)	3/8"(9.5mm)	60
NS05-9636	3/8"(9.5mm)	4-1/2"(116mm)	3/8"(9.5mm)	36
NS05-9624	3/8"(9.5mm)	4-1/2"(116mm)	3/8"(9.5mm)	24
NS05-9616	3/8"(9.5mm)	4-1/2"(116mm)	3/8"(9.5mm)	16

Also available with 6mm and 9mm shaft

1/4" Shaft Balls & Wheels



NS05-5324 NS05-5224 NS05-5124 NS05-5024

Ref No.	Shape	Head Diameter	Head Length	Shaft	Grits
NS05-5036	Ball	7/8"(22.2mm)	7/8"(22.2mm)	1/4"(6.3mm)	36
NS05-5024	Ball	7/8"(22.2mm)	7/8"(22.2mm)	1/4"(6.3mm)	24
NS05-5016	Ball	7/8"(22.2mm)	7/8"(22.2mm)	1/4"(6.3mm)	16
NS05-5124	Wheel	1-3/8"(34.9mm)	1/4"(6.3mm)	1/4"(6.3mm)	24
NS05-5224	Wheel	1-5/8"(41.2mm)	1/4"(6.3mm)	1/4"(6.3mm)	24
NS05-5324	Wheel	2"(50.8mm)	1/4"(6.3mm)	1/4"(6.3mm)	24

Also available with 6mm shaft

Sanding Discs



NS05-1724

Ref No.	Diameter	Bore	Grits
NS05-1036	4-5/8"(115mm)	7/8"(22.2mm)	36
NS05-1024	4-5/8"(115mm)	7/8"(22.2mm)	24
NS05-1016	4-5/8"(115mm)	7/8"(22.2mm)	16
NS05-1136	5"(125mm)	7/8"(22.2mm)	36
NS05-1124	5"(125mm)	7/8"(22.2mm)	24
NS05-1116	5"(125mm)	7/8"(22.2mm)	16
NS05-1736	7"(180mm)	7/8"(22.2mm)	36
NS05-1724	7"(180mm)	7/8"(22.2mm)	24
NS05-1716	7"(180mm)	7/8"(22.2mm)	16

Rotary Gouges



GO050

GO030

Ref No.	Diameter	Bore	Description
GO030	1-1/4"(30mm)	3/8"(9.5mm)	Rotary gouge Mini
GO050	2"(50mm)	3/8"(9.5mm)	Standard thin wall gouge

Adapters



NS-AD-001

NS-AD-002

NS-AD-003

NS-AD-004

NS-AD-005

NS-AD-006

NS-AD-007

NS-AD-008

Ref No.	Description
NS-AD-001	3/8"-24 thread to 6mm adapter, suitable for buffing tools with 3/8" thread
NS-AD-002	3/8"-24 thread to 6.3mm adapter, suitable for buffing tools with 3/8" thread
NS-AD-003	3/8"-24 thread to arbor NV11, 13mm thread length, suitable for buffing tools with 3/8" thread, Quick change adapter
NS-AD-004	3/8"-24 thread to arbor NV11, 25mm thread length, suitable for buffing tools with 3/8" thread, Quick change adapter
NS-AD-005	3/8"-24 thread to arbor NV11, 45mm thread length, suitable for buffing tools with 3/8" thread, Quick change adapter
NS-AD-006	1/8" to arbor NV11, suitable for all tools with 1/8" shaft, Quick change adapter
NS-AD-007	M14 to arbor NV11, suitable for buffing tools with M14 bore, Quick change adapter
NS-AD-008	6mm to arbor NV11, suitable for buffing tools with 6mm shaft, Quick change adapter

High Precision Range

Multiple shapes available with different sizes of regular grits.

Possibility to produce customized products.

Comparison chart	
Traditional grits	High precision grits
Grit 16	Grit 390
Grit 24	Grit 330
Grit 36	Grit 230
Grit 60	Grit 170



NS120

NS109

NS104

Contour Wheels

Ref No.	Diameter	Width	Bore	Grits
NS102	2" (50.8mm)	3/4"(19mm)	3/8"(9.5mm)	170
NS104	2" (50.8mm)	3/4"(19mm)	3/8"(9.5mm)	230
NS105	2" (50.8mm)	3/4"(19mm)	3/8"(9.5mm)	390
NS107	2-1/2"(63.1mm)	1-1/16"(26.9mm)	3/8"(9.5mm)	170
NS109	2-1/2"(63.1mm)	1-1/16"(26.9mm)	3/8"(9.5mm)	230
NS111	2-1/2"(63.1mm)	1-1/16"(26.9mm)	3/8"(9.5mm)	390
NS118	3-1/2"(88.9mm)	1-1/2"(38.1mm)	3/8"(9.5mm)	170
NS120	3-1/2"(88.9mm)	1-1/2"(38.1mm)	3/8"(9.5mm)	230
NS122	3-1/2"(88.9mm)	1-1/2"(38.1mm)	3/8"(9.5mm)	390



NS101

NS140

Buffing Domes

Ref No.	Diameter	Width	Bore	Grits
NS100	1-3/4" (44.4mm)	3/4"(19mm)	3/8" x 24 thread	170
NS101	1-3/4" (44.4mm)	3/4"(19mm)	3/8" x 24 thread	230
NS140	1-1/4" (31.7mm)	3/4"(19mm)	3/8" x 24 thread	170
NS142	1-1/4" (31.7mm)	3/4"(19mm)	3/8" x 24 thread	230



NS312

NS308

NS304

NS300

Flat Wheels

Ref No.	Diameter	Width	Bore	Grits
NS300	2" (50.8mm)	1/4"(6.3mm)	3/8" x 24 thread	230
NS302	2" (50.8mm)	1/4"(6.3mm)	3/8" x 24 thread	390
NS304	2" (50.8mm)	3/8"(9.5mm)	3/8" x 24 thread	230
NS306	2" (50.8mm)	3/8"(9.5mm)	3/8" x 24 thread	390
NS308	2" (50.8mm)	1/2"(12.7mm)	3/8" x 24 thread	230
NS310	2" (50.8mm)	1/2"(12.7mm)	3/8" x 24 thread	390
NS312	2" (50.8mm)	3/4"(19mm)	3/8" x 24 thread	230
NS314	2" (50.8mm)	3/4"(19mm)	3/8" x 24 thread	390

Unit Wheels



Ref No.	Diameter	Length	Shaft	Grits
NS200	3"(76.2mm)	1"(25.4mm)	9/16"(14mm)	230
NS202	3"(76.2mm)	1"(25.4mm)	9/16"(14mm)	390



Tapered Cone Rasps

Ref No.	Diameter	Length	Bore	Grits
NS501	5/8"(15.8mm)	1-3/8"(34.9mm)	3/8" x 24 thread	230
NS503	5/8"(15.8mm)	1-3/8"(34.9mm)	3/8" x 24 thread	390
NS505	7/8"(22.2mm)	2"(50.8mm)	3/8" x 24 thread	230
NS507	7/8"(22.2mm)	2"(50.8mm)	3/8" x 24 thread	390
NS509	7/8"(22.2mm)	4"(101.6mm)	3/8" x 24 thread	230
NS511	7/8"(22.2mm)	4"(101.6mm)	3/8" x 24 thread	390



Pencil Rasps

Ref No.	Diameter	Length	Shaft	Grits
NS625	1/4"(6.3mm)	3"(76.2mm)	1/4"(6.3mm)	230
NS626	1/4"(6.3mm)	3"(76.2mm)	1/4"(6.3mm)	330
NS627	3/8"(9.5mm)	3"(76.2mm)	3/8"(9.5mm)	230
NS628	3/8"(9.5mm)	3"(76.2mm)	3/8"(9.5mm)	330



1/4" Shaft Balls, Tapers & Wheels

Ref No.	Shape	Head Diameter	Head Length	Shaft	Grits
NS600	Ball	5/8"(15.8mm)	5/8"(15.8mm)	1/4"(6.3mm)	230
NS601	Ball	5/8"(15.8mm)	5/8"(15.8mm)	1/4"(6.3mm)	330
NS602	Ball	7/8"(22.2mm)	7/8"(22.2mm)	1/4"(6.3mm)	230
NS603	Ball	7/8"(22.2mm)	7/8"(22.2mm)	1/4"(6.3mm)	330
NS610	Taper	5/8"(15.8mm)	1"(25.4mm)	1/4"(6.3mm)	230
NS611	Taper	5/8"(15.8mm)	1"(25.4mm)	1/4"(6.3mm)	330
NS612	Taper	7/8"(22.2mm)	1-1/4"(31.7mm)	1/4"(6.3mm)	230
NS613	Taper	7/8"(22.2mm)	1-1/4"(31.7mm)	1/4"(6.3mm)	330
NS619	Wheel	1-3/8"(34.9mm)	1/4"(6.3mm)	1/4"(6.3mm)	330
NS620	Wheel	1-5/8"(41.2mm)	1/4"(6.3mm)	1/4"(6.3mm)	330
NS621	Wheel	2"(50.8mm)	1/4"(6.3mm)	1/4"(6.3mm)	330

Also available with 6mm shaft



1/8" Shaft Rotaries

Ref No.	Shape	Head Diameter	Head Length	Shaft	Grits
NS638	Rotor Saw	3/4"(19mm)	1/8"(3.1mm)	1/8"(3.1mm)	170
NS639	Ball	3/8"(9.5mm)	3/8"(9.5mm)	1/8"(3.1mm)	170
NS636	Taper	1/8"(3.1mm)	7/8"(22.2mm)	1/8"(3.1mm)	170
NS637	Taper	1/4"(6.3mm)	5/8"(15.8mm)	1/8"(3.1mm)	170
NS635	1/8" shaft rotary kit: 1 x NS638, 1 x NS639, 1 x NS636, 1 x NS637				

Also available with 3mm shaft



NS708

Donut Wheels

Ref No.	Diameter	Width	Bore	Grits
NS708	6"(152.4mm)	1"(25.4mm)	1-1/2"(38.1mm)	390



NS71230

Sanding Discs

Ref No.	Diameter	Bore	Grits
NS71170	4-5/8"(115mm)	7/8"(22.2mm)	170
NS71230	4-5/8"(115mm)	7/8"(22.2mm)	230
NS71390	4-5/8"(115mm)	7/8"(22.2mm)	390
NS74170	7"(180mm)	7/8"(22.2mm)	170
NS74230	7"(180mm)	7/8"(22.2mm)	230
NS74390	7"(180mm)	7/8"(22.2mm)	390



NS156

NS152

NS151

Interior Plugs for Contour Wheels

Ref No.	Diameter	Bore	Description
NS151	2"(50.8mm)	3/8"(9.5mm)	Guide for contour wheel NS 102, NS 104 and NS105
NS152	2-1/2"(63.1mm)	3/8"(9.5mm)	Guide for contour wheel NS 107, NS 109 and NS 111
NS156	3-1/2"(88.9mm)	3/8"(9.5mm)	Guide for contour wheel NS 118, NS120 and NS 122

Carbide Cutters



CARB12

CARB10

CARB08

CARB06

CARB045

CARB03

Ref No.	Diameter	Blade length	Total length
CARB03	3mm	30mm	60mm
CARB045	4.5mm	50mm	80mm
CARB06	6mm	55mm	90mm
CARB08	8mm	60mm	105mm
CARB10	10mm	65mm	110mm
CARB12	12mm	70mm	110mm



- Only use the low speed air buffers (max 5000 rpm) with Go Retread products.
- Always use approved safety devices!
- Measurement of tools is based on blank body.

